


Datasheet for: 103572



Brass ball valve, Pneumat. actuation drive, single-acting, Rp 1/2

Brass ball valve, Pneumat. actuation drive, single-acting, Operating temperature -20 °C to 150 °C, Rp 1/2, DN 15, PN max. 16 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Type number	351.310
Article number	103572
EAN/barcode	 4047322078740
Your price	203,39 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	221.0 mm
Angle of rotation	90 °
B	110.0 mm
DN	15.0
L	69.0 mm
Material actuator	Anodised aluminium
Material ball valve	Nickel-plated brass, with ISO flange plate
Max. operating pressure	16 bar
Max. operating temperature	150 °C
Max. pilot pressure	5.6 bar
Max. temperature range	80 °C
Min. operating temperature	-20 °C
Min. temperature range	-20 °C
Page No.	WEB
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 1/2
Valve adapter	Supplied as standard
Version	single-acting - spring to close

Variants

Article number	Thread	DN	Price
103572	Rp 1/2	15.0	203,39 € / Stk
103571	Rp 3/8	10.0	201,64 € / Stk
103573	Rp 3/4	20.0	208,04 € / Stk
103574	Rp 1	25.0	215,72 € / Stk
103575	Rp 1 1/4	32.0	239,27 € / Stk
103576	Rp 1 1/2	40.0	262,56 € / Stk
103577	Rp 2	50.0	348,52 € / Stk

More Pictures

