


Datasheet for: 103589


Stainless steel ball valve, Pneumatic actuation drive, Rp 1/2

Stainless steel ball valve, Pneumatic actuation drive, single-acting, Operating temp. -20 °C to 150 °C, Rp 1/2, PN max. 160 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Type number	351.520
Article number	103589
EAN/barcode	 4047322078917
Your price	270,86 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	221.0 mm
Angle of rotation	90 °
B	147.0 mm
DN	15.0
L	61.0 mm
Material actuator	Anodised aluminium
Material ball valve	Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange
Max. operating temperature	150 °C
Max. pilot pressure	5.6 bar
Max. temperature range	80 °C
Min. operating temperature	-20 °C
Min. temperature range	-20 °C
PN	160 bar
Page No.	WEB
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 1/2
Valve adapter	Supplied as standard
Version	single-acting - spring to close

Variants

Article number	Thread	DN	PN	Price
103589	Rp 1/2	15.0	160 bar	270,86 € / Stk
103588	Rp 3/8	10.0	160 bar	267,35 € / Stk
103590	Rp 3/4	20.0	100 bar	338,27 € / Stk
103591	Rp 1	25.0	100 bar	364,96 € / Stk
103592	Rp 1 1/4	32.0	64 bar	433,57 € / Stk
103593	Rp 1 1/2	40.0	64 bar	515,58 € / Stk
103594	Rp 2	50.0	40 bar	705,33 € / Stk
154078	Rp 1/2	15.0	100 bar	278,99 € / Stk
154075	Rp 3/8	10.0	100 bar	275,37 € / Stk

More Pictures

