


Datasheet for: 103691


End position feedback type SC-M 2, micro-switch, 250 V AC

End position feedback type SC-M 2, micro-switch, 250 V AC, Changeover contact, Current range 16 A, IP 66, Temp. -20 °C to 70 °C . Robust type in an aluminium housing - Universal indicator for NAMUR sizes 80 x 30 and 130 x 30 - Height-adjustable feet that adapt to different pinion projections - ON / OFF position indicator also visible from a distance - Easy-to-adjust, self-locking trip cam

Type number	350.930
Article number	103691
EAN/barcode	 4047322078214
Your price	115,36 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Cable gland	M20x1.5, up to four cable glands possible
Current range	Max. 5 A
Description	End position feedback, SC-M 2 type with microswitch
Housing	Die-cast aluminium EN AB 46100, epoxy powder-coated
Max. temperature range	70 °C
Min. temperature range	-20 °C
Page No.	WEB
Protection IP	EX TDA21 IP66/67 T 85 °C
Screws	Stainless steel
Shaft	Nickel-plated steel
Switching function	Changeover, silver-plated contacts
Version	with double microswitch
Voltage range	Max. 250 V AC