

Datasheet for: 174096




Filter regulator »Standard« Metal container, 40 μm , Size 4, G 3/4

Filter regulator »Standard«, Metal container and pressure gauge, 40 μm , Size 4, G 3/4, PE max. 25 bar, 0.5 - 16 bar, pilot contr. . Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Type number 678.42 M P

Article number 174096

EAN/barcode



4047322658591

Your price 275,71 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	125.0 mm
Bowl	Metal container
C	129.0 mm
Condensate drain	Manuel
D	265.6 mm
DN	25.0
Filter rating	40.0 μm
Flow rate	12000 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	16.0 bar
Max. input pressure	25 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	WEB
Pressure gauge display max.	25.0 bar

Pressure gauge
 display min. 0.0 bar
 Sealant NBR
 Series Standard
 Size 4
 Thread G 3/4

Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	Price
174096	G 3/4	Aluminium, painted silver	40.0 μm	12000 l/min	4	275,71 € / Stk
100934	G 1/4	Die-cast zinc, painted silver	5.0 μm	900 l/min	1	59,65 € / Stk
100935	G 3/8	Die-cast zinc, painted silver	5.0 μm	900 l/min	1	59,65 € / Stk
100936	G 3/8	Die-cast zinc, painted silver	40.0 μm	1500 l/min	2	104,50 € / Stk
100937	G 1/2	Die-cast zinc, painted silver	5.0 μm	3000 l/min	3	104,50 € / Stk
100938	G 3/4	Aluminium, painted silver	40.0 μm	7000 l/min	4	275,71 € / Stk
100939	G 1	Aluminium, painted silver	40.0 μm	7000 l/min	4	275,71 € / Stk
174097	G 1	Aluminium, painted silver	40.0 μm	12000 l/min	4	275,71 € / Stk

More Pictures

