


Datasheet for: 174101


Service unit 2-part »Standard«, Protective cage, Size 4, G 1

Service unit 2-part »Standard«, PC container, protective cage, Size 4, G 1, PE max. 16 bar, Control range 0.5 - 10 bar, pilot con. . Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	866 S P
Article number	174101
EAN/barcode	 4047322658515
Your price	415,98 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	222.0 mm
B	392.0 mm
Bowl	Polycarbonate container with protective cage
C	129.0 mm
Condensate drain	Semi-automatic
DN	25.0
Filter rating	40.0 μm
Flow rate	4000 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc / aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	WEB
Pressure gauge display max.	16.0 bar

Pressure gauge display min.	0.0 bar
Pressure gauge Ø	63 mm
Sealant	NBR
Series	Standard
Sight dome	PA
Size	4
Thread	G 1

Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
174101	G 1	40.0 µm	4000 l/min	4	25.0	415,98 € / Stk
101052	G 1/4	5.0 µm	600 l/min	1	6.0	117,32 € / Stk
101053	G 3/8	5.0 µm	600 l/min	1	6.0	117,32 € / Stk
101054	G 3/8	40.0 µm	800 l/min	2	10.0	191,37 € / Stk
101055	G 1/2	5.0 µm	2100 l/min	3	15.0	191,37 € / Stk
101056	G 3/4	40.0 µm	4000 l/min	4	20.0	415,98 € / Stk
101057	G 1	40.0 µm	4000 l/min	4	25.0	415,98 € / Stk

More Pictures

