


## Datasheet for: 178361


**Service unit 2-part »GA-mini«, 5  $\mu\text{m}$ , Size 200, G 1/8, 1.5 - 9 bar**

Service unit 2-part »GA-mini«, with PC container, 5  $\mu\text{m}$ , Size 200, G 1/8, Input pressure max. 10 bar, Control range 1.5 - 9 bar . Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	GACL 05
Article number	178361
EAN/barcode	 4047322666329
Your price	83,00 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	108.0 mm
B	171.0 mm
C	73.0 mm
Condensate drain	Semi-automatic
D	98.0 mm
Filter rating	5.0 $\mu\text{m}$
Flow rate	900 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Housing	Die-cast aluminium
Max. control range	9.0 bar
Max. input pressure	10 bar
Max. temperature range	70 °C
Min. control range	1.5 bar
Min. temperature range	-5 °C
Page No.	WEB
Sealant	NBR
Series	GA-mini
Sight dome	Brass/POM
Size	200

Spring bonnet  
Thread

POM  
G 1/8

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
178361	G 1/8	83,00 € / Stk
178362	G 1/4	83,00 € / Stk

## More Pictures

