


## Datasheet for: 178502


**Service unit 2-part »GA«, Metal container, 5  $\mu\text{m}$ , Size 600, G 1**

Service unit 2-part »GA«, Metal container, Viewing tube, 5  $\mu\text{m}$ , Size 600, G 1, Input pressure max. 10 bar, Control range 1.5-9 bar . Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	GACL 55
Article number	178502
EAN/barcode	 4047322666992
Your price	254,19 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	206.0 mm
B	336.5 mm
Bowl	Metal container with viewing tube
C	131.5 mm
Condensate drain	Semi-automatic
D	205.0 mm
Filter rating	5.0 $\mu\text{m}$
Flow rate	6000 l/min
Flow rate measurement	At $P_1 = 8 \text{ bar}$ , $P_2 = 6 \text{ bar}$ and pressure drop $\Delta_p = 1 \text{ bar}$
Housing	Die-cast aluminium
Max. control range	9.0 bar
Max. input pressure	10 bar
Max. temperature range	70 °C
Min. control range	1.5 bar
Min. temperature range	-5 °C
Page No.	WEB
Sealant	NBR
Series	GA
Sight dome	Brass/POM

Size  
 Spring bonnet  
 Thread

600  
 POM  
 G 1

## Variants

Article number	Thread	Flow rate	Size	Condensate drain	Price
178502	G 1	6000 l/min	600	Semi-automatic	254,19 € / Stk
178504	G 1	6000 l/min	600	Fully-automatic	276,43 € / Stk
178501	G 3/4	6000 l/min	600	Semi-automatic	254,19 € / Stk
178503	G 3/4	6000 l/min	600	Fully-automatic	276,43 € / Stk

## More Pictures

