


Datasheet for: 178506


Service unit 3-part »GA«, PC container, 5 µm, Size 300, G 3/8

Service unit 3-part »GA«, PC container, Protective cage, 5 µm, Size 300, G3/8, Input pressure max. 10 bar, Control range 1.5-9 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	GAFRL 12
Article number	178506
EAN/barcode	 4047322667036
Your price	93,01 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	195.0 mm
B	203.5 mm
Bowl	Polycarbonate container with protective cage
C	45.5 mm
Condensate drain	Semi-automatic
D	158.0 mm
Filter rating	5.0 µm
Flow rate	2000 l/min
Flow rate measurement	At P ₁ = 8 bar, P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Housing	Die-cast aluminium
Max. control range	9.0 bar
Max. input pressure	10 bar
Max. temperature range	70 °C
Min. control range	1.5 bar
Min. temperature range	-5 °C
Page No.	WEB
Sealant	NBR
Series	GA
Sight dome	Brass/POM
Size	300
Spring bonnet	POM

Thread

G 3/8

Variants

Article number	Thread	Flow rate	Size	Condensate drain	Price
178506	G 3/8	2000 l/min	300	Semi-automatic	93,01 € / Stk
178513	G 3/8	3500 l/min	400	Fully-automatic	174,47 € / Stk
178514	G 1/2	3500 l/min	400	Fully-automatic	174,47 € / Stk
178511	G 3/8	2000 l/min	300	Fully-automatic	131,05 € / Stk
178510	G 1/4	1550 l/min	300	Fully-automatic	131,05 € / Stk
178508	G 3/8	3500 l/min	400	Semi-automatic	138,86 € / Stk
178512	G 1/2	2000 l/min	300	Fully-automatic	131,05 € / Stk
178509	G 1/2	3500 l/min	400	Semi-automatic	138,86 € / Stk
178507	G 1/2	2000 l/min	300	Semi-automatic	93,01 € / Stk
178505	G 1/4	1550 l/min	300	Semi-automatic	93,01 € / Stk

More Pictures

