

## Datasheet for: 178508



### Service unit 3-part »GA«, PC container, 5 µm, Size 400, G 3/8

Service unit 3-part »GA«, PC container, Protective cage, 5 µm, Size 400, G3/8, Input pressure max. 10 bar, Control range 1.5-9 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | GAFRL 32                                                                                           |
| Article number | 178508                                                                                             |
| EAN/barcode    | <br>4047322667050 |
| Your price     | 138,86 € / Stk                                                                                     |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                        |                                                                      |
|------------------------|----------------------------------------------------------------------|
| A                      | 248.0 mm                                                             |
| B                      | 227.0 mm                                                             |
| Bowl                   | Polycarbonate container with protective cage                         |
| C                      | 49.5 mm                                                              |
| Condensate drain       | Semi-automatic                                                       |
| D                      | 177.5 mm                                                             |
| Filter rating          | 5.0 µm                                                               |
| Flow rate              | 3500 l/min                                                           |
| Flow rate measurement  | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Housing                | Die-cast aluminium                                                   |
| Max. control range     | 9.0 bar                                                              |
| Max. input pressure    | 10 bar                                                               |
| Max. temperature range | 70 °C                                                                |
| Min. control range     | 1.5 bar                                                              |
| Min. temperature range | -5 °C                                                                |
| Page No.               | WEB                                                                  |
| Sealant                | NBR                                                                  |
| Series                 | GA                                                                   |
| Sight dome             | Brass/POM                                                            |
| Size                   | 400                                                                  |
| Spring bonnet          | POM                                                                  |

Thread

G 3/8

## Variants

| Article number | Thread | Flow rate  | Size | Condensate drain | Price          |
|----------------|--------|------------|------|------------------|----------------|
| 178508         | G 3/8  | 3500 l/min | 400  | Semi-automatic   | 138,86 € / Stk |
| 178513         | G 3/8  | 3500 l/min | 400  | Fully-automatic  | 174,47 € / Stk |
| 178514         | G 1/2  | 3500 l/min | 400  | Fully-automatic  | 174,47 € / Stk |
| 178511         | G 3/8  | 2000 l/min | 300  | Fully-automatic  | 131,05 € / Stk |
| 178510         | G 1/4  | 1550 l/min | 300  | Fully-automatic  | 131,05 € / Stk |
| 178512         | G 1/2  | 2000 l/min | 300  | Fully-automatic  | 131,05 € / Stk |
| 178509         | G 1/2  | 3500 l/min | 400  | Semi-automatic   | 138,86 € / Stk |
| 178506         | G 3/8  | 2000 l/min | 300  | Semi-automatic   | 93,01 € / Stk  |
| 178507         | G 1/2  | 2000 l/min | 300  | Semi-automatic   | 93,01 € / Stk  |
| 178505         | G 1/4  | 1550 l/min | 300  | Semi-automatic   | 93,01 € / Stk  |

## More Pictures

