


Datasheet for: 178516


Service unit 3-part »GA«, Metal container, 5 µm, Size 600, G 1

Service unit 3-part »GA«, Metal container, Viewing tube, 5 µm, Size 600, G 1, Input pressure max. 10 bar, Control range 1.5-9 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	GAFRL 55
Article number	178516
EAN/barcode	 4047322667135
Your price	294,93 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	312.0 mm
B	267.5 mm
Bowl	Metal container with viewing tube
C	62.5 mm
Condensate drain	Semi-automatic
D	205.0 mm
Filter rating	5.0 µm
Flow rate	4800 l/min
Flow rate measurement	At P ₁ = 8 bar, P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Housing	Die-cast aluminium
Max. control range	9.0 bar
Max. input pressure	10 bar
Max. temperature range	70 °C
Min. control range	1.5 bar
Min. temperature range	-5 °C
Page No.	WEB
Sealant	NBR
Series	GA
Sight dome	Brass/POM
Size	600
Spring bonnet	POM

Thread

G 1

Variants

Article number	Thread	Flow rate	Size	Condensate drain	Price
178516	G 1	4800 l/min	600	Semi-automatic	294,93 € / Stk
178517	G 3/4	4800 l/min	600	Fully-automatic	317,17 € / Stk
178518	G 1	4800 l/min	600	Fully-automatic	317,17 € / Stk
178515	G 3/4	4800 l/min	600	Semi-automatic	294,93 € / Stk

More Pictures

