

Datasheet for: 102552


Capsule pressure gauge, rear centric, G 1/4, - 250 mbar, Ø 63

Capsule pressure gauge, Housing steel, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range - 250 mbar, Ø 63 . With zero correction.

Type number	5825
Article number	102552
EAN/barcode	 4047322102827
Your price	92,84 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.6
Applications	For gaseous, dry, non-corrosive media
Connection	G 1/4
Connection position	rear, central
Diameter	63 mm
Front glass	Plexiglass
Housing	Steel, black
Lower / Upper range limit	Positive pressure
Max. ambient temperature	60 °C
Max. medium temperature	100 °C
Measuring element	Copper alloy
Measuring range max. mbar	250.0
Measuring range min. mbar	0.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK221
Scale graduation in the mbar area	10.0 mbar
Type	611.10
Version	Capsule-type pressure gauge

Variants

Article number	Housing	Max. medium temperature	Measuring range max. mbar	Diameter	Connection	Price
102552	Steel, black	100 °C	250.0	63 mm	G 1/4	92,84 € / Stk
102548	Steel, black	100 °C	40.0	63 mm	G 1/4	92,84 € / Stk
102549	Steel, black	100 °C	60.0	63 mm	G 1/4	92,84 € / Stk
102550	Steel, black	100 °C	100.0	63 mm	G 1/4	92,84 € / Stk
102551	Steel, black	100 °C	160.0	63 mm	G 1/4	92,84 € / Stk
102553	Steel, black	100 °C	400.0	63 mm	G 1/4	92,84 € / Stk
102554	CrNi steel	80 °C	25.0	100 mm	G 1/2	121,95 € / Stk
102555	CrNi steel	80 °C	40.0	100 mm	G 1/2	121,95 € / Stk
102556	CrNi steel	80 °C	60.0	100 mm	G 1/2	121,95 € / Stk
102557	CrNi steel	80 °C	100.0	100 mm	G 1/2	121,95 € / Stk
102558	CrNi steel	80 °C	160.0	100 mm	G 1/2	121,95 € / Stk
102559	CrNi steel	80 °C	250.0	100 mm	G 1/2	121,95 € / Stk
102560	CrNi steel	80 °C	400.0	100 mm	G 1/2	121,95 € / Stk