

Datasheet for: 102567


Micrometre pressure gauge, radial bottom, G 1/2, 0-2.5 bar, Ø 160

Micrometre pressure gauge, Connection radial bottom, G 1/2, Goods class 0.6, Measurement range 0-2.5 bar, Ø 160 . Bourdon-tube pressure gauge for precision measurements. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	1162
Article number	102567
EAN/barcode	 4047322021074
Your price	324,07 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	0.6
Bezel	CrNi steel
Connection	G 1/2
Connection position	radial on bottom
Diameter	160 mm
Front glass	Flat instrument glass
Housing	CrNi steel
Lower / Upper range limit	Positive pressure
Max. ambient temperature	60 °C
Max. medium temperature	80 °C
Measuring element	Copper alloy
Measuring range max. bar	2.5
Measuring range min. bar	0.0
Min. ambient temperature	-40 °C
Movement	Copper alloy
Page No.	HK222
Scale graduation in the bar area	0.02 bar
Type	312.20

Variants

Article number	Measuring range min. bar	Measuring range max. bar	Scale graduation in the bar area	Price
102567	0.0	2.5	0.02 bar	324,07 € / Stk
102561	-1.0	0.0	0.0 bar	324,07 € / Stk
102562	-1.0	0.6	0.01 bar	324,07 € / Stk
102563	-1.0	1.5	0.02 bar	324,07 € / Stk
102564	0.0	0.6	0.0 bar	324,07 € / Stk
102565	0.0	1.0	0.0 bar	324,07 € / Stk
102566	0.0	1.6	0.01 bar	324,07 € / Stk
102568	0.0	4.0	0.02 bar	324,07 € / Stk
102569	0.0	6.0	0.05 bar	271,78 € / Stk
102570	0.0	10.0	0.05 bar	271,78 € / Stk
102571	0.0	16.0	0.1 bar	271,78 € / Stk
102572	0.0	25.0	0.2 bar	271,78 € / Stk
102573	0.0	40.0	0.2 bar	271,78 € / Stk
102574	0.0	60.0	0.5 bar	349,01 € / Stk
102575	0.0	160.0	1.0 bar	349,01 € / Stk
102576	0.0	250.0	2.0 bar	349,01 € / Stk
102577	0.0	400.0	2.0 bar	349,01 € / Stk