


## Datasheet for: 102578


**Differential pressure gauge, parallel, 2 x G 1/2, 0-1 bar, Ø 100**

Differential pressure gauge, 2 parallel radial male end connections below, G 1/2, Goods class 1.6, Measurement range 0-1 bar, Ø100 . Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems. For measuring differential pressures or two different pressures. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	1201
Article number	102578
EAN/barcode	 4047322022316
Your price	138,38 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Accuracy class	1.6
Bezel	Steel, black
Connection	G 1/2
Connection position	radial on bottom
Diameter	100 mm
Front glass	Flat instrument glass
Housing	Steel, black
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Copper alloy
Measuring range max. bar	1.0
Measuring range min. bar	0.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK222
Scale graduation in the bar area	0.02 bar
Type	711.12

## Variants

<i>Article number</i>	<i>Measuring range max. bar</i>	<i>Price</i>
102578	1.0	138,38 € / Stk
102579	1.6	138,38 € / Stk
102580	2.5	138,38 € / Stk
102581	4.0	138,38 € / Stk
102582	6.0	138,38 € / Stk
102583	10.0	138,38 € / Stk