


Datasheet for: 102584



Diaphragm pressure gauge, Robust design, G 1/2, -1/+1.5 bar, Ø100

Diaphragm pressure gauge, Robust design, Connection radial bottom, G 1/2, Goods class 1.6, Measurement range -1 / +1.5 bar, Ø100 . Diaphragm pressure gauge in robust design or for chemical applications. Suitable for gaseous or liquid media, chemical applications type also suitable for use in corrosive atmosphere.

Type number	PL 1901
Article number	102584
EAN/barcode	 4047322163255
Your price	154,11 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.6
Bezel	CrNi steel, black
Connection	G 1/2
Connection position	radial on bottom
Diameter	100 mm
Front glass	Flat instrument glass
Housing	Grey cast iron, black
Lower / Upper range limit	Vacuum/Positive pressure
Max. ambient temperature	60 °C
Max. medium temperature	100 °C
Measuring element	CrNi steel
Measuring flange diameter	100 mm
Measuring range max. bar	1.5
Measuring range min. bar	-1.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK223

Scale graduati-
on in the bar
area
Type

0.05 bar
422.12

Variants

<i>Article number</i>	<i>Measuring range min. bar</i>	<i>Measuring range max. bar</i>	<i>Price</i>
102584	-1.0	1.5	154,11 € / Stk
102585	0.0	1.0	154,11 € / Stk
102586	0.0	1.6	154,11 € / Stk
102587	0.0	2.5	154,11 € / Stk
102588	0.0	4.0	154,11 € / Stk
102589	0.0	6.0	154,11 € / Stk
102590	0.0	10.0	154,11 € / Stk
102591	0.0	16.0	154,11 € / Stk
102592	0.0	25.0	154,11 € / Stk