

Datasheet for: 102586


Diaphragm pressure gauge, Robust design, G 1/2, 0-1.6 bar, Ø 100

Diaphragm pressure gauge, Robust design, Connection radial bottom, G 1/2, Goods class 1.6, Measurement range - 1.6 bar, Ø 100 . Diaphragm pressure gauge in robust design or for chemical applications. Suitable for gaseous or liquid media, chemical applications type also suitable for use in corrosive atmosphere.

Type number	PL 1912
-------------	---------

Article number	102586
----------------	--------

EAN/barcode



4047322163279

Your price	154,11 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.6
Bezel	CrNi steel, black
Connection	G 1/2
Connection position	radial on bottom
Diameter	100 mm
Front glass	Flat instrument glass
Housing	Grey cast iron, black
Lower / Upper range limit	Positive pressure
Max. ambient temperature	60 °C
Max. medium temperature	100 °C
Measuring element	CrNi steel
Measuring flange diameter	100 mm
Measuring range max. bar	1.6
Measuring range min. bar	0.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK223

Scale graduation in the bar area
Type

0.05 bar
422.12

Variants

<i>Article number</i>	<i>Measuring range min. bar</i>	<i>Measuring range max. bar</i>	<i>Price</i>
102586	0.0	1.6	154,11 € / Stk
102584	-1.0	1.5	154,11 € / Stk
102585	0.0	1.0	154,11 € / Stk
102587	0.0	2.5	154,11 € / Stk
102588	0.0	4.0	154,11 € / Stk
102589	0.0	6.0	154,11 € / Stk
102590	0.0	10.0	154,11 € / Stk
102591	0.0	16.0	154,11 € / Stk
102592	0.0	25.0	154,11 € / Stk