


Datasheet for: 102641


Block valve pressure gauge, Bushing-Bushing, bright brass, G 1/4

Block valve pressure gauge, Bushing - Bushing, made of bright brass, G 1/4, PN 6 bar, AF 17, max. 50 °C . It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Type number	9002
Article number	102641
EAN/barcode	 4047322122689
Your price	11,88 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Applications	For all pressure gauges with a flat gasket acc. to DIN 16258
Hand lever	Plastic
Housing	Brass with a bare metal surface
Max. temperature range	50 °C
PN	6 bar
Page No.	HK227
Thread	G 1/4
Version	female / female
a/f	17 mm

Variants

Article number	Thread	PN	a/f	Housing	Standard	Test flange	Price
102641	G 1/4	6 bar	17 mm	Brass with a bare metal surface			11,88 € / Stk
102642	G 3/8	16 bar	22 mm	Brass with a bare metal surface			14,22 € / Stk

Variants

Article number	Thread	PN	a/f	Housing	Standard	Test flange	Price
102643	G 1/2	25 bar	27 mm	Brass with a bare metal surface	DIN 16261-A		17,12 € / Stk
102644	G 1/2	25 bar	27 mm	Stainless steel 1.4571	DIN 16261-A		90,98 € / Stk
102645	G 1/2	25 bar	27 mm	Brass with a bare metal surface		60x25x10	27,84 € / Stk
102646	G 1/2	25 bar	27 mm	Brass with a bare metal surface		40x5	27,84 € / Stk