


Datasheet for: 102646


Block valve pressure gauge, Bushing-Bushing, bright brass, G 1/2

Block valve pressure gauge, Bushing - Bushing, made of bright brass, G 1/2, PN 25 bar, AF 27, max. 50 °C, Test flange 40x5 . It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

| | |
|----------------|--|
| Type number | 9005/40 |
| Article number | 102646 |
| EAN/barcode |  4047322122726 |
| Your price | 27,84 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|------------------------|--|
| Applications | For all pressure gauges with a flat gasket acc. to DIN 16258 |
| Hand lever | Plastic |
| Housing | Brass with a bare metal surface |
| Max. temperature range | 50 °C |
| PN | 25 bar |
| Page No. | HK227 |
| Test flange | 40x5 |
| Thread | G 1/2 |
| Version | female / female, with test flange 40x5 |
| a/f | 27 mm |

Variants

| Article number | Thread | PN | a/f | Housing | Standard | Test flange | Price |
|----------------|--------|--------|-------|---------------------------------|----------|-------------|---------------|
| 102646 | G 1/2 | 25 bar | 27 mm | Brass with a bare metal surface | | 40x5 | 27,84 € / Stk |

Variants

| Article number | Thread | PN | a/f | Housing | Standard | Test flange | Price |
|----------------|--------|--------|-------|---------------------------------|-------------|-------------|---------------|
| 102641 | G 1/4 | 6 bar | 17 mm | Brass with a bare metal surface | | | 11,88 € / Stk |
| 102642 | G 3/8 | 16 bar | 22 mm | Brass with a bare metal surface | | | 14,22 € / Stk |
| 102643 | G 1/2 | 25 bar | 27 mm | Brass with a bare metal surface | DIN 16261-A | | 17,12 € / Stk |
| 102644 | G 1/2 | 25 bar | 27 mm | Stainless steel 1.4571 | DIN 16261-A | | 90,98 € / Stk |
| 102645 | G 1/2 | 25 bar | 27 mm | Brass with a bare metal surface | | 60x25x10 | 27,84 € / Stk |