


Datasheet for: 149058


Inline pressure regulator, 2 x IT, G 3/8, pre-set 7 bar

Inline pressure regulator, 2 x IT, with secondary venting, Pre-pressure dependent, G 3/8, Working pressure (pre-set) 7 bar . The majority of pneumatic tools are connected directly to the compressed air supply by means of a quick disconnect coupling, in other words they tend to be supplied with a higher pressure than is actually required. Which increases consumption and leads to tool overload. Added safety is provided by the automatic self-relieving function. If the tool is disconnected from the hose, it continues to work for a short period, even though it has been switched off, owing to the residual pressure that is present on the tool side. Inadvertent operation of the tool can thus lead to serious injuries to the user (tackers or nail drivers can fire up to another ten shots). This effect can be prevented by using the inline pressure regulators, which have a preset pressure determined by the application, thereby achieving energy efficiency and economy.

Type number	638.17
Article number	149058
EAN/barcode	 4047322583961
Your price	59,80 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	63.0 mm
Flow rate	2400 l/min
Housing	Aluminium
Internal parts	Stainless steel, nitrile rubber, brass
Max. operating pressure	25 bar
Max. temperature range	80 °C
Page No.	HK174
Series	inline
Thread	G 3/8
Working pressure (preset)	7.0 bar
a/f 1	22.0 mm
a/f 2	25.0 mm

Variants

Article number	Thread	Working pressure (preset)	Flow rate	a/f 1	a/f 2	Price
149058	G 3/8	7.0 bar	2400 l/min	22.0 mm	25.0 mm	59,80 € / Stk
101477	G 1/4	5.0 bar	650 l/min	16.0 mm	19.0 mm	46,69 € / Stk
101485	G 1/2	4.0 bar	1800 l/min	27.0 mm	30.0 mm	63,80 € / Stk
101486	G 1/2	6.0 bar	2200 l/min	27.0 mm	30.0 mm	63,80 € / Stk
101474	G 1/4	2.0 bar	500 l/min	16.0 mm	19.0 mm	46,69 € / Stk
101478	G 1/4	6.0 bar	700 l/min	16.0 mm	19.0 mm	46,69 € / Stk
101476	G 1/4	4.0 bar	600 l/min	16.0 mm	19.0 mm	46,69 € / Stk
101483	G 3/8	8.0 bar	2600 l/min	22.0 mm	25.0 mm	59,80 € / Stk
101475	G 1/4	3.0 bar	550 l/min	16.0 mm	19.0 mm	46,69 € / Stk
101482	G 3/8	6.0 bar	2200 l/min	22.0 mm	25.0 mm	59,80 € / Stk
101481	G 3/8	4.0 bar	1800 l/min	22.0 mm	25.0 mm	59,80 € / Stk
101480	G 3/8	2.0 bar	1400 l/min	22.0 mm	25.0 mm	59,80 € / Stk
101479	G 1/4	8.0 bar	800 l/min	16.0 mm	19.0 mm	46,69 € / Stk
101484	G 1/2	2.0 bar	1400 l/min	27.0 mm	30.0 mm	63,80 € / Stk
101487	G 1/2	8.0 bar	2600 l/min	27.0 mm	30.0 mm	63,80 € / Stk
149061	G 1/2	7.0 bar	2400 l/min	27.0 mm	30.0 mm	63,80 € / Stk
149057	G 3/8	5.0 bar	2000 l/min	22.0 mm	25.0 mm	59,80 € / Stk
149059	G 1/2	3.0 bar	1600 l/min	27.0 mm	30.0 mm	63,80 € / Stk
149064	G 3/4	6.0 bar	3900 l/min	34.0 mm	40.0 mm	198,72 € / Stk
149063	G 3/4	4.0 bar	3200 l/min	34.0 mm	40.0 mm	198,72 € / Stk
149055	G 1/4	7.0 bar	750 l/min	16.0 mm	19.0 mm	46,69 € / Stk
149060	G 1/2	5.0 bar	2000 l/min	27.0 mm	30.0 mm	63,80 € / Stk
149062	G 3/4	2.0 bar	2500 l/min	34.0 mm	40.0 mm	198,72 € / Stk
149056	G 3/8	3.0 bar	1600 l/min	22.0 mm	25.0 mm	59,80 € / Stk
149065	G 3/4	8.0 bar	4600 l/min	34.0 mm	40.0 mm	198,72 € / Stk

More Pictures

