

Datasheet for: 102651


Block valve pressure gauge, Bushing - taps, bright brass, G 1/2

Block valve pressure gauge, Bushing - taps, made of bright brass, G 1/2, PN 25 bar, AF 27, max. 50 °C, Test flange 60x25x10 . It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Type number	9010/60
Article number	102651
EAN/barcode	 4047322122801
Your price	28,30 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Applications	For all pressure gauges with a flat gasket acc. to DIN 16258
Hand lever	Plastic
Housing	Brass with a bare metal surface
Max. temperature range	50 °C
PN	25 bar
Page No.	HK227
Test flange	60x25x10
Thread	G 1/2
Version	female / male, with test flange 60x25x10
a/f	27 mm

Variants

Article number	Thread	PN	a/f	Housing	Standard	Test flange	Price
102651	G 1/2	25 bar	27 mm	Brass with a bare metal surface		60x25x10	28,30 € / Stk

Variants

Article number	Thread	PN	a/f	Housing	Standard	Test flange	Price
102647	G 1/4	6 bar	17 mm	Brass with a bare metal surface			12,00 € / Stk
102648	G 3/8	16 bar	22 mm	Brass with a bare metal surface			14,43 € / Stk
102649	G 1/2	25 bar	27 mm	Brass with a bare metal surface	DIN 16261-B		16,54 € / Stk
102650	G 1/2	25 bar	27 mm	Stainless steel 1.4571	DIN 16261-B		89,69 € / Stk