

Datasheet for: 102656


Block valve pressure gauge, taps - tension sleeve, G 1/4

Block valve pressure gauge, Taps - tension sleeve, bright brass housing, steel tension sleeve, G 1/4, PN 6 bar, AF 17, max. 50 °C . It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Type number	9020/M
Article number	102656
EAN/barcode	 4047322122955
Your price	16,19 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Applications	For all pressure gauges with a flat gasket acc. to DIN 16258
Female/female connector	Phosphatised steel
Hand lever	Plastic
Housing	Brass with a bare metal surface
Max. temperature range	50 °C
PN	6 bar
Page No.	HK227
Standard	DIN 16262-B
Thread	G 1/4
Version	male / female/female
a/f	17 mm

Variants

Article number	Thread	PN	a/f	Housing	Standard	Test flange	Price
----------------	--------	----	-----	---------	----------	-------------	-------

Variants

Article number	Thread	PN	a/f	Housing	Standard	Test flange	Price
102656	G 1/4	6 bar	17 mm	Brass with a bare metal surface	DIN 16262-B		16,19 € / Stk
102657	G 1/2	25 bar	27 mm	Brass with a bare metal surface	DIN 16262-A		19,81 € / Stk
102658	G 1/2	25 bar	27 mm	Stainless steel 1.4571	DIN 16262-A		90,98 € / Stk
102659	G 1/2	25 bar	27 mm	Brass with a bare metal surface		60x25x10	29,59 € / Stk
102660	G 1/2	25 bar	27 mm	Stainless steel 1.4571		60x25x10	130,93 € / Stk
102661	G 1/2	25 bar	27 mm	Brass with a bare metal surface		40x5	32,51 € / Stk