

Datasheet for: 102659


Block valve pressure gauge, taps - tension sleeve, G 1/2

Block valve pressure gauge, Taps-tension sleeve, br. body, steel t. sleeve, G1/2, PN 25bar, AF 27, max. 50°C, Test flange 60x25x10 . It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Type number	9022/M
Article number	102659
EAN/barcode	 4047322122993
Your price	29,59 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Applications	For all pressure gauges with a flat gasket acc. to DIN 16258
Female/female connector	Phosphatised steel
Hand lever	Plastic
Housing	Brass with a bare metal surface
Max. temperature range	50 °C
PN	25 bar
Page No.	HK227
Test flange	60x25x10
Thread	G 1/2
Version	male / female/female, with test flange 60x25x10
a/f	27 mm

Variants

Article number	Thread	PN	a/f	Housing	Standard	Test flange	Price
----------------	--------	----	-----	---------	----------	-------------	-------

Variants

Article number	Thread	PN	a/f	Housing	Standard	Test flange	Price
102659	G 1/2	25 bar	27 mm	Brass with a bare metal surface		60x25x10	29,59 € / Stk
102656	G 1/4	6 bar	17 mm	Brass with a bare metal surface	DIN 16262-B		16,19 € / Stk
102657	G 1/2	25 bar	27 mm	Brass with a bare metal surface	DIN 16262-A		19,81 € / Stk
102658	G 1/2	25 bar	27 mm	Stainless steel 1.4571	DIN 16262-A		90,98 € / Stk
102660	G 1/2	25 bar	27 mm	Stainless steel 1.4571		60x25x10	130,93 € / Stk
102661	G 1/2	25 bar	27 mm	Brass with a bare metal surface		40x5	32,51 € / Stk