

## Datasheet for: 102672


**Blocking valve pressure gauge, taps-tension sleeve, brass, G 1/2**

Blocking valve pressure gauge, Taps - tension sleeve, with test flange 60x25x10, brass, G 1/2, PN 250 bar, AF 27, max. 120 °C . Used as shut-off or reducing elements for pressure gauges when measuring liquids, gases or steam.

Type number	9185/M
Article number	102672
EAN/barcode	 4047322123433
Your price	32,03 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Female/female connector	Steel
Housing	Brass
Max. operating temperature	120 °C
Min. operating temperature	-10 °C
PN	250 bar
Page No.	HK228
Sealant	PTFE
Thread	G 1/2
Union nut	Steel
Valve cone	Stainless steel
Valve stem	Stainless steel
Version	male / female/female, with test flange 60x25x10
Wheel	Plastic
a/f	27 mm

## Variants

<i>Article number</i>	<i>Housing</i>	<i>PN</i>	<i>Price</i>
102672	Brass	250 bar	32,03 € / Stk
102673	Stainless steel 1.4571	400 bar	108,45 € / Stk