

## Datasheet for: 151352


**Straight Check valve »Blue Series«, Thread to hose, G 1/4 O.**

Straight Check valve »Blue Series«, Thread to hose, G 1/4 o., for hose exterior Ø 8 mm, Working pressure max. 10 bar, sleeve red . The non-return function of these push-in fittings prevents the air from flowing back, the unidirectional design means air flow is only possible in one direction. These valves are available with air flow from the port to the tube or from the tube to the port.

Type number	200.148-1
Article number	151352
EAN/barcode	 4047322591980
Your price	5,61 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Applications	Air, vacuum
For tube O.D.	8 mm
L1	36.9 mm
Material	Plastic and nickel-plated brass
Max. temperature range	60 °C
Max. working pressure	10 bar
Medium	Compressed air
Min. opening pressure	0.2 bar
Page No.	WEB
Recommended hose	PU or PA (nylon)
Series	Blue series
Sleeve	Plastic red
Standard thread	DIN EN ISO 228-1
Thread	G 1/4
a/f	15 mm

## Variants

<i>Article number</i>	<i>Thread</i>	<i>For tube O.D.</i>	<i>a/f</i>	<i>Price</i>
151352	G 1/4	8 mm	15 mm	5,61 € / Stk
151587	M5	4 mm	10 mm	3,79 € / Stk

## More Pictures

