


Datasheet for: 151516


Straight Check valve »Blue Series«, Hose to thread, G 3/8 O.

Straight Check valve »Blue Series«, Hose to thread, G 3/8 o., for hose exterior Ø 12 mm, Working pressure max. 10 bar . The non-return function of these push-in fittings prevents the air from flowing back, the unidirectional design means air flow is only possible in one direction. These valves are available with air flow from the port to the tube or from the tube to the port.

Type number	201.3812-2
Article number	151516
EAN/barcode	 4047322593724
Your price	12,04 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Applications	Air, vacuum
For tube O.D.	12 mm
L1	44.5 mm
Material	Plastic and nickel-plated brass
Max. temperature range	60 °C
Max. working pressure	10 bar
Medium	Compressed air
Min. opening pressure	0.2 bar
Page No.	HK689
Recommended hose	PU or PA (nylon)
Series	Blue series
Sleeve	Plastic blue
Standard thread	DIN EN ISO 228-1
Thread a/f	G 3/8 20 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>For tube O.D.</i>	<i>a/f</i>	<i>Price</i>
151516	G 3/8	12 mm	20 mm	12,04 € / Stk
151518	G 1/2	12 mm	24 mm	13,70 € / Stk
151511	G 1/8	6 mm	14 mm	4,76 € / Stk
151515	G 3/8	10 mm	20 mm	10,49 € / Stk
151514	G 1/4	8 mm	17 mm	8,37 € / Stk
151512	G 1/8	8 mm	14 mm	5,53 € / Stk
151509	M5	4 mm	10 mm	3,98 € / Stk
151510	G 1/8	4 mm	14 mm	4,71 € / Stk
151517	G 1/2	10 mm	24 mm	11,68 € / Stk
151513	G 1/4	6 mm	17 mm	8,27 € / Stk

More Pictures

