

Cleanflow magnet static – Automatic cleaning – Discontinuous – Dust proof – Ex II 1/2D

SECD – 3232 – 07Q – N – F1H – B – P – B – B

Product	
SECD	Cleanflow magnet static, auto cleaning – Discontinuous – Dust proof
SECDZ	Special Cleanflow magnet static, auto cleaning – Discontinuous – Dust proof

Connection size	
....	Square in/outlet .. x .. [cm] (3232 = 320 x 320mm)

Magnetic bars	
07 ...	Number of magnetic bars
... P	Magnetic bars Pneumatically operated d25mm
... Q	Magnetic bars Pneumatically operated d34mm
... Z	Magnetic bars special

Magnet quality	
N	N42, Br 13.300 gauss, Tmax 80°C
HT	N42SH, Br 13.300 gauss, Tmax 150°C
ET	N30EH, Br 11.400 gauss, Tmax 200°C
ES	N52, Br 14.800 gauss, Tmax 80°C

Finishing: Surface treatment & Welds	
See info chart 'Finishing Surface treatment & Welds'	

Fe-outlet	
B	Basic: no valve box
V	With Valve box
Z	Special Fe-outlet

Control	
P	Pneumatic
L	Siemens Logo control

Coating	
B	Basic (no coating)
W	Wear resistant with Tungsten carbide coating on magnet(s)
T	Wear resistant with Tungsten carbide coating on magnet(s) and housing
H	Hard inchromating on magnet(s)
I	Hard inchromating on magnet(s) and housing
Z	Special coating

Detection / sensors	
B	Basic (no sensors)
E	Single bar detection sensor (1 bar)
F	Full bar detection sensors (all bars)
Z	Special sensor