



Magnetic filters, industrial

SFN-065-IF-04E-HT-F1m-S-B-B

SKU: SSFN006538

Product Features

Description	Neoflux® quick-cleaning magnetic filter
SKU	SSFN006538
Product key	SFN-065-IF-04E-HT-F1m-S-B-B
Max. particle size	10 mm
Min. Fe-particle size that can be caught	30 µm
Cleaning/Fe-particles disposal	Manual quick cleaning by means of extractor tubes
Build-in length	228 mm
Interface/connection dim's	DN65 acc. EN 1092-1 PN16
Materials - in contact with product	AISI316L (SS 1.4404)
Material housing	AISI304 (SS 1.4301), AISI316L (SS 1.4404)
Magnetic bar joint	Extractor tubes not brazed in plate (welded only)
Material gaskets/seals	Silicone VMQ O-ring, 70° Shore, red, 'Food Safe' acc. EC 1935/2004 and FDA
Surface treatment/finishing	S1: Grit blasted, Ra 3 µm (interior/exterior)
Welds	Wm: product chute: completely welded - outside the product chute: completely welded where possible
Max. operating / product temperature	140 °C
Min./max. ambient temperature	-10 to 40 °C
Operating pressure	Max. 10 bar
Test pressure	15 bar
Magnetic system	Magnetic bar in extractor tube

Visit our website for specifications, drawings, documentation, accessories, spare parts and more

<https://www.goudsmitmagnets.com/solutions/magnetic-filtering-separating/pressure-filter-magnets/industrial-manual.html?sku=SSFN006538>

Magnetic bar size	Tube Ø25 mm; bar Ø23 mm
No of bars	4
Magnet quality	Neodymium GSN-42SH, Br 13,300 gauss (at 20 °C), Tmax. 150 °C
Field strength (flux density) on magnetic bar (±10%)	10700 gauss
Field strength (flux density) on extractor tube (±10%)	8000 (average value - see Documents tab for explanation) gauss
Length	228 mm
Width	187 mm
Height	230 mm
Weight	13 kg

Visit our website for specifications, drawings, documentation, accessories, spare parts and more

<https://www.goudsmitmagnets.com/solutions/magnetic-filtering-separating/pressure-filter-magnets/industrial-manual?sku=SSFN006538>