



## Magnetic bars

BAR-HT-23-550-25-2M6-NW-B

SKU: SBANA100020-550

## Product Features

<b>Description</b>	Neoflux® magnetic bar Ø23
<b>SKU</b>	SBANA100020-550
<b>Product key</b>	BAR-HT-23-550-25-2M6-NW-B
<b>Min. Fe-particle size that can be caught</b>	30 µm
<b>Cleaning/Fe-particles disposal</b>	Manually
<b>Interface/connection dim's</b>	Threaded hole M6 (2x)
<b>Material tube</b>	AISI316L (SS 1.4404)
<b>Surface treatment/finishing</b>	S9: Manually polished (interior/exterior), Ra 0,4 µm (excluding welds and end faces outside the product chute)
<b>Welds</b>	WM: all welds: completely welded
<b>Max. operating / product temperature</b>	140 °C
<b>Dust/water protection class</b>	IP67
<b>Pitch magnets</b>	25 mm
<b>Magnet quality</b>	GSN-42SH Neodymium, Br 13,300 gauss (at 20 °C), Tmax. 150 °C
<b>Field strength (flux density) on magnetic bar (±10%)</b>	10700 gauss
<b>Diameter</b>	23 mm
<b>Length</b>	550 mm
<b>Weight</b>	1.7 kg

Visit our website for specifications, drawings, documentation, accessories, spare parts and more

<https://www.goudsmitmagnets.com/solutions/magnetic-filtering-separating/bar-magnets.html?sku=SBANA100020-550>