



## Magnetic bars

BAR-N-23-300-25-2M8-NW-B

SKU: SBAMA100040-300

## Product Features

<b>Description</b>	Neoflux® magnetic bar Ø23
<b>SKU</b>	SBAMA100040-300
<b>Product key</b>	BAR-N-23-300-25-2M8-NW-B
<b>Min. Fe-particle size that can be caught</b>	30 µm
<b>Cleaning/Fe-particles disposal</b>	Manually
<b>Interface/connection dim's</b>	Threaded hole M8 (2x)
<b>Material tube</b>	AISI316L (SS 1.4404)
<b>Surface treatment/finishing</b>	S9: Manually polished (interior/exterior), Ra 0,4 µm (excluding welds and end faces outside the product chute)
<b>Welds</b>	WM: all welds: completely welded
<b>Max. operating / product temperature</b>	60 °C
<b>Dust/water protection class</b>	IP67
<b>Pitch magnets</b>	25 mm
<b>Magnet quality</b>	GSN-42 Neodymium, Br 13,300 gauss (at 20 °C), Tmax. 80 °C
<b>Field strength (flux density) on magnetic bar (±10%)</b>	10700 gauss
<b>Diameter</b>	23 mm
<b>Length</b>	300 mm
<b>Weight</b>	0.94 kg