



## Sheet separators ferrite

HSS-F-BA-154x047-0530-B

SKU: TBSP030530

### Product Features

<b>Description</b>	Ferrite magnetic sheet separator
<b>SKU</b>	TBSP030530
<b>Product key</b>	HSS-F-BA-154x047-0530-B
<b>Max. sheet thickness</b>	4 mm
<b>Max. stack height</b>	490 mm
<b>Recommended working surface (for clean sheets)</b>	40 dm <sup>2</sup>
<b>Recommended working surface (for sticky sheets)</b>	26 dm <sup>2</sup>
<b>Interface/connection dim's</b>	Threaded hole M8 (3x)
<b>Material housing</b>	AISI304 (SS 1.4301),S235JRC+C (St 1.0122)
<b>Surface treatment/finishing</b>	Painted
<b>Colour</b>	Red (Traffic red): RAL3020
<b>Min./max. ambient temperature</b>	-20 to 100 °C
<b>Magnetic system</b>	2 Permanent magnet poles with flux control
<b>Magnet quality</b>	Anisotropic ferrite GSFD-33, Br 4100 gauss (at 20 °C), Tmax. 225 °C
<b>Length</b>	530 mm
<b>Width</b>	154 mm
<b>Weight</b>	20 kg
<b>Depth</b>	47 mm

Visit our website for specifications, drawings, documentation, accessories, spare parts and more

<https://www.goudsmitmagnets.com/solutions/magnetic-handling/sheet-separators/sheet-separators-ferrite.html?sku=TBSP030530>