



Cleanflows manual cleaning - Static

SECF-B-3030-11E-N-F1E-W-S-B

SKU: SECF300438

Product Features

Description	Cleanflow magnet - manual cleaning - static
SKU	SECF300438
Product key	SECF-B-3030-11E-N-F1E-W-S-B
Туре	Basic
In-/outlet shape	Square
Max. particle size	10 mm
Min. Fe-particle size that can be caught	30 µm
Cleaning/Fe-particles disposal	Manual quick cleaning by means of extractor tubes
Build-in length	160 mm
Product inlet/outlet size	#296 mm
Interface/connection dim's	Square flange - 20xM8
Capacity	12 to 30 m³/h
Materials - in contact with product	AISI316 (SS 1.4401),AISI316L (SS 1.4404)
Material housing	AISI316L (SS 1.4404)
Magnetic bar joint	Extractor tubes laser welded in plate
Material gaskets/seals	Silicone VMQ, 40° Shore, red, 'Food Safe' acc. EC 1935/2004 and FDA
Surface treatment/finishing	S1: Grit blasted, Ra 3 µm (interior/exterior)
Welds	WE: product chute: completely welded - outside the product chute: intermittently welded
Max. operating / product temperature	0°C
Min./max. ambient temperature	-20 to 60 °C

Visit our website for specifications, drawings, documentation, accessories, spare parts and more https://www.goudsmitmagnets.com/solutions/magnetic-filtering-separating/cleanflow-grid-magnets/manual-static.html?sku=SECF300438



Magnetic system	Magnetic bar in extractor tube
Magnetic bar size	Tube Ø25 mm; bar Ø23 mm
No of bars	11 (5+6)
Magnet quality	Neodymium GSN-42, Br 13,300 gauss (at 20 $^\circ$ C), Tmax. 80 $^\circ$ C
Field strength (flux density) on magnetic bar (±10%)	10700 gauss
Field strength (flux density) on extractor tube (±10%)	8000 (average value - see Documents tab for explanation) gauss
Depth	380 mm
Width	440 mm
Height	160 mm
Weight	28 kg
ATEX-Marking	Free of own ignition sources: suitable for application in ATEX dust zones 20, 21 and 22. Special conditions apply.