




Ferrite overband magnets

ROP-F5-C-160-W-G-L-B-B-B-NA

SKU: ROFC160350

Product Features

Description	Ferrite permanent overband magnetic separator
SKU	ROFC160350
Product key	ROP-F5-C-160-W-G-L-B-B-B-NA
Type	5
Suitable for	Cross mounting
Min. Fe-particle size that can be caught	1 mm
Advised max. installation height	400 mm
Cleaning/Fe-particles disposal	Fully automatic with continuous production process
Suitable for belt width	1600 mm
Interface/connection dim's	Lifting eye Ø35 mm (8x)
Material	Stainless steel (covering), Steel (framework), Steel (magnet enclosure)
Surface treatment/finishing	Painted, Grit blasted (covering)
Colour	Dark grey (Black grey): RAL7021 (frame and rollers), Red (Traffic red): RAL3020 (magnet/motor), - (covering)
Max. operating / product temperature	100 °C
Min./max. ambient temperature	-20 to 40 °C
Conveying length	2480 mm
Conveyor (belt) speed	1,5 m/s
Belt type	Rubber, with cleats (EP500/3 6+2mm)
Belt width	1000 mm
Magnetic system	Permanent ferrite magnet

Visit our website for specifications, drawings, documentation, accessories, spare parts and more

<https://www.goudsmitmagnets.com/solutions/magnetic-recycling-sorting/overband-magnetic-separators/ferrite.html?sku=ROFC160350>

Magnet dimensions	1860x951x343 mm
Main pole dimensions	1660x951x343 mm
Magnet quality	Anisotropic ferrite GSFD-33, Br 4100 gauss (at 20 °C), Tmax. 225 °C
Motor power supply	230/400 V AC; 50 Hz; 3.0 kW
Motor drive	Electro motor with gear box: SEW SA67/T DRN100L4
Motor mounting position	M1B - 0/1
Motor rotational speed	In/out: 1456/71 rpm
Motor electrical thermal insulation class	ISO-B (130 °C)
Motor dust/water protection class	IP54
Duty cycle	100%, 24 hours/day
Length	3200 mm
Width	1620 mm
Height	745 mm
Weight	3150 kg

Visit our website for specifications, drawings, documentation, accessories, spare parts and more

<https://www.goudsmitmagnets.com/solutions/magnetic-recycling-sorting/overband-magnetic-separators/ferrite.html?sku=ROFC160350>