



## Pressure-tight Cleanflows manual cleaning - Static

SECF-P-1212-05E-N-F1m-W-B-B

SKU: SECFP12030

## **Product Features**

Description Cleanflow magnet - pressure tight - manual cleaning - static SKU SECFP12030 **Product key** SECF-P-1212-05E-N-F1m-W-B-B In-/outlet shape Square Max. particle size 10 mm Min. Fe-particle size that can be caught 30 µm Cleaning/Fe-particles disposal Manual quick cleaning by means of extractor tubes 160 mm **Build-in length** Product inlet/outlet size #120 mm Interface/connection dim's Flange #160x#120 mm - 8xM6 (ready for Jacob system 'spouts from square to round' DN100) 2 to 6 m<sup>3</sup>/h Capacity Materials - in contact with product AISI316 (SS 1.4401), AISI316L (SS 1.4404) **Material housing** AISI316 (SS 1.4401), AISI316L (SS 1.4404), Bakelite (knob) Extractor tubes not brazed in plate (welded only) Magnetic bar joint Material gaskets/seals Silicone VMQ, 40° Shore, red, 'Food Safe' acc. EC 1935/2004 and FDA Surface treatment/finishing S1: Grit blasted, Ra 3 µm (interior/exterior) Welds Wm: product chute: completely welded - outside the product chute: completely welded where possible Max. operating / product temperature 60 °C Min./max. ambient temperature -20 to 60 °C



zones 20, 21 and 22. Special conditions apply.

Max. 1.5 bar **Operating pressure Magnetic system** Magnetic bar in extractor tube Magnetic bar size Tube Ø25 mm; bar Ø23 mm No of bars 5 (2+3) Neodymium GSN-42, Br 13,300 gauss (at 20 °C), Tmax. 80 °C **Magnet quality** Field strength (flux density) on magnetic bar 10700 gauss (±10%) Field strength (flux density) on extractor tube 8000 (average value - see Documents tab for explanation) gauss (±10%) 207 mm **Depth** Width 248 mm Height 160 mm Weight 8 kg **ATEX-Marking** 2Free of own ignition sources: suitable for application in ATEX dust