

Datasheet for: 108139



Kamlok quick-connect plug, Interior thread, A type, 1.4401, G 3/4

Kamlok quick-connect plug with interior thread, A type, Stainless steel 1.4401, G 3/4, Plug Ø 32 mm, Pressure max. 16 bar . High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection. A male part and a female part are joined together by shifting the handles. There is no need to turn the hose! Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc. All female threaded couplings and connectors are with female thread sealing ring made of PTFE.

Type number	1117.34-ES
Article number	108139
EAN/barcode	 4047322404792
Your price	7,29 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

L	36.0 mm
Max. operating pressure	16 bar
Max. temperature range	95 °C
Min. temperature range	-20 °C
Page No.	HK624
Plug Ø	32 mm
Sealant	NBR, resistant to oils and benzine
Thread	G 3/4

Variants

Article number	Thread	Plug Ø	Price
108139	G 3/4	32 mm	7,29 € / Stk
108145	G 3	92 mm	45,65 € / Stk
108146	G 4	120 mm	77,05 € / Stk
108142	G 1 1/2	53 mm	16,95 € / Stk
108140	G 1	37 mm	10,12 € / Stk
108141	G 1 1/4	46 mm	13,72 € / Stk
108143	G 2	63 mm	25,02 € / Stk
108144	G 2 1/2	76 mm	38,01 € / Stk

More Pictures

