

Datasheet for: 102798


Bi-metallic thermometer, rear, L1=63 mm / L2=43 mm, Ø 100

Bi-metallic thermometer, High quality design, Connection rear, for protective pipe L1=63 mm / L2=43 mm, Display range 0°C to 160°C . Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems. A thermowell (removable with locking screw) is required.

Type number	5243
Article number	102798
EAN/barcode	 4047322099080
Your price	31,34 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Bezel	CrNi steel
Connection	Flush, with collar for thermowell, Ø 18 mm
Connection position	rear
Diameter	100 mm
Display correction	Trimming pointer
Front glass	Flat instrument glass
Housing	CrNi steel
Indicating range max.	160 °C
Operating pressure	Max. 25 bar (on thermowell)
Page No.	HK239
Scale graduation in the bar area	1.0 bar
Stem	Ø 8 mm, CrNi steel
Suitable for thermowell with length	L1 = 63.0 mm / L2 = 43.0 mm
Type	52

Variants

Article number	Indicating range min.	Indicating range max.	Suitable for thermowell with length	Diameter	Price
102798	°C	160 °C	L1 = 63.0 mm / L2 = 43.0 mm	100 mm	31,34 € / Stk
102783	-30 °C	50 °C	L1 = 63.0 mm / L2 = 43.0 mm	63 mm	25,52 € / Stk
102784	°C	120 °C	L1 = 63.0 mm / L2 = 43.0 mm	63 mm	20,62 € / Stk
102785	°C	160 °C	L1 = 63.0 mm / L2 = 43.0 mm	63 mm	25,52 € / Stk
102786	°C	200 °C	L1 = 63.0 mm / L2 = 43.0 mm	63 mm	25,52 € / Stk
102787	°C	250 °C	L1 = 63.0 mm / L2 = 43.0 mm	63 mm	27,73 € / Stk
102788	-30 °C	50 °C	L1 = 100.0 mm / L2 = 80.0 mm	63 mm	26,68 € / Stk
102789	°C	120 °C	L1 = 100.0 mm / L2 = 80.0 mm	63 mm	21,76 € / Stk
102790	°C	160 °C	L1 = 100.0 mm / L2 = 80.0 mm	63 mm	26,68 € / Stk
102791	°C	200 °C	L1 = 100.0 mm / L2 = 80.0 mm	63 mm	26,68 € / Stk
102792	°C	250 °C	L1 = 100.0 mm / L2 = 80.0 mm	63 mm	29,14 € / Stk
102793	-30 °C	50 °C	L1 = 160.0 mm / L2 = 140.0 mm	63 mm	28,77 € / Stk
102794	°C	120 °C	L1 = 160.0 mm / L2 = 140.0 mm	63 mm	25,52 € / Stk
102795	°C	160 °C	L1 = 160.0 mm / L2 = 140.0 mm	63 mm	27,73 € / Stk
102796	-30 °C	50 °C	L1 = 63.0 mm / L2 = 43.0 mm	100 mm	32,61 € / Stk
102797	°C	120 °C	L1 = 63.0 mm / L2 = 43.0 mm	100 mm	28,77 € / Stk
102799	°C	250 °C	L1 = 63.0 mm / L2 = 43.0 mm	100 mm	34,82 € / Stk
102800	-30 °C	50 °C	L1 = 100.0 mm / L2 = 80.0 mm	100 mm	34,82 € / Stk
102801	°C	120 °C	L1 = 100.0 mm / L2 = 80.0 mm	100 mm	29,14 € / Stk
102802	°C	160 °C	L1 = 100.0 mm / L2 = 80.0 mm	100 mm	32,72 € / Stk
102803	°C	200 °C	L1 = 100.0 mm / L2 = 80.0 mm	100 mm	34,82 € / Stk
102804	°C	250 °C	L1 = 100.0 mm / L2 = 80.0 mm	100 mm	35,64 € / Stk
102805	-30 °C	50 °C	L1 = 160.0 mm / L2 = 140.0 mm	100 mm	35,75 € / Stk
102806	°C	120 °C	L1 = 160.0 mm / L2 = 140.0 mm	100 mm	30,75 € / Stk
102807	°C	160 °C	L1 = 160.0 mm / L2 = 140.0 mm	100 mm	34,82 € / Stk
102808	°C	200 °C	L1 = 160.0 mm / L2 = 140.0 mm	100 mm	35,75 € / Stk
102809	°C	250 °C	L1 = 160.0 mm / L2 = 140.0 mm	100 mm	38,20 € / Stk