


Datasheet for: 108546

Pivoting suction pad attachment »flexolink«, G 1/4 IT, G 1/4 ET

Pivoting suction pad attachment »flexolink«, G 1/4 IT, G 1/4 ET, Steel / rubber, Bracket 12°, Bending moment 10 N . Flexible suction pad mounting By flexing in all directions, this mounting allows the suction pad to better adapt itself to sloping workpieces. Advantages:

- Very good adaptation to sloping workpiece surfaces
 - Automatically resets into the initial position
 - Vacuum-tight design with integrated protection against damage
- Applications:
- Handling workpieces with sloping surfaces using large-area suction pads
 - Handling large sheets of materials that may sag when lifted
 - Can be used together with spring plungers to compensate for differing workpiece heights and uneven surfaces



Type number	FLK 1414
Article number	108546
EAN/barcode	 4047322200653
Your price	31,81 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Angle	12 °
Bending moment	10 N
H	27.0 mm
L1	12.0 mm
L2	12.0 mm
Material	Steel, rubber
Page No.	WEB
Thread 1	G 1/4 IT
Thread 2	G 1/4 ET
Vertical load	750 N
Weight	30.0 g
a/f	17 mm

Variants

Article number	Thread 2	Vertical load	Bending moment	Price
108546	G 1/4 ET	750 N	10 N	31,81 € / Stk
108545	M10x1.25 ET	500 N	8 N	33,30 € / Stk

More Pictures

