


Datasheet for: 116585


2/2-way solenoid valve »2W« NC, directly operated, 24 V DC, G 1/4

2/2-way solenoid valve »2W«, Brass, NC, directly operated, 24 V DC, Medium temperature max. 80 °C / 90 °C, G 1/4, PN - 30 bar . Standard series available in two different versions: -Directly operated -Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media. Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

| | |
|----------------|--|
| Type number | MVH 1512 |
| Article number | 116585 |
| EAN/barcode |  4047322324663 |
| Your price | 38,77 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|-----------------------------------|
| A | 70.0 mm |
| B | 40.0 mm |
| C | 70.7 mm |
| DN | 1.5 |
| Housing | Brass |
| Internal parts | Stainless steel |
| Max. operating pressure | 30 bar |
| Page No. | HK324 |
| Page No. AS | AS046 |
| Protection IP | IP 65 |
| Sealant | FPM |
| Standard thread | G thread acc. to DIN EN ISO 228-1 |
| Thread | G 1/4 |
| Type | 1 |
| Valve seat | Brass |

Variants

| <i>Article number</i> | <i>Thread</i> | <i>DN</i> | <i>Price</i> |
|-----------------------|---------------|-----------|---------------|
| 116585 | G 1/4 | 1.5 | 38,77 € / Stk |
| 116589 | G 1/2 | 3 | 55,23 € / Stk |
| 116587 | G 3/8 | 3 | 55,23 € / Stk |
| 116583 | G 1/8 | 1.5 | 38,77 € / Stk |

More Pictures

